

JINAN EMI SHIELDING TECHNOLOGY CO.,LTD.

EMI SHIELDING CONDUCTIVE ADHESIVE TAPE

Conductive fabric adhesive tape


Maxi Width:1000mm Maxi Length:100Metre

Adhesive thickness:0.035mm Liner thickness:0.15mm

conductive fabric thickness:0.085mm Resistivity:Less 0.05ohm/sq

Peel strength :1.6kg/25mm

- 1.Backing non-conductive adhesive
- 2.Backing nickle conductive adheisve(<0.03ohm/sq)



Copper foil adhesive tape

Maxi Width:990mm Maxi Length:100Metre

Adhesive thickness:0.035mm Liner thickness:0.15mm

Copper thickness:0.025- 0.1mm Resistivity:Less 0.05ohm/sq

Peel strength :1.6kg/25mm

- 1.Backing non-conductive adhesive
- 2.Backing nickle conductive adheisve(<0.03ohm/sq)



Aluminiu foil adhesive tape


Maxi Width:990mm Maxi Length:100Metre

Adhesive thickness:0.035mm Liner thickness:0.15mm

foil thickness:0.030-0.1mm Resistivity:Less 0.06ohm/sq

Peel strength :1.6kg/25mm

- 1.Backing non-conductive adhesive
- 2.Backing nickle conductive adheisve(<0.03ohm/sq)



Address:No.51 ,shandabei Road ,Jinan,Shandong China 250100

Tel:0086-531-81901321 Fax:0086-531-81901393

E-mail:info@emishielding.com.cn

Website:www.emishielding.com.cn